MIDDLE EAR ANALYZER











THE MODELS

Clarinet is available in two models: Basic and Plus. The following table is an overview of the tests available on each version.

	Basic	Plus
Automatic tympanometry	✓	✓
Manual tympanometry	✓	✓
Multi-component tympanometry (Y, B, G, B/G)	-	✓
Automatic acoustic reflex thresholds	✓	✓
Manual acoustic reflex	✓	✓
Acoustic reflex decay	✓	✓
Acoustic reflex latency	✓	✓
Quick tests (tymp. + reflex sequence)	✓	✓
Eustachian tube function (intact / perforated)	✓	✓
Probe tones	226Hz	226 Hz, 678 Hz 800 Hz, 1000 Hz





Clarinet is developed by:

INVENTIS s.r.l.

CORSO STATI UNITI, 1/3 35127 PADOVA – ITALY

PHONE: +39.049.8962 844 FAX: +39.049.8966 343

info@inventis.it www.inventis.it

Follow us on Twitter http://twitter.com/inventissrl



The Inventis Quality System complies with ISO 9001 and ISO 13485 standards.

investigation to new levels.

ENDLESS FLOW PUMP

Clarinet immediately impresses for the incredible speed of its pump: the sweep speed can reach 600 daPa / sec, without compromising on accuracy and precision of tympanogram plots. The pump features an endless airflow technology, improving the execution of the test when the seal is not optimal.

GO IN-DEPTH WITH INVESTIGATIONS

High-frequency and multi-component

tympanometry, evaluation of multiple

stimuli averaged reflex latencies

together with the up-to-date measure of reflex plot angles of incidence are

just some of the Clarinet advanced

features that will take your clinical



Clarinet features an extremely light, small and sturdy metal probe, which can be very rapidly disassembled and cleaned. The probe is connected to the small Control Box, through which you can select the ear and start the exam.

NOAH & DAISY INTEGRATION

Simply connect Clarinet to a USB port on your computer (no driver needed), and you can transfer exam results into your Daisy or Noah database. And with the live view feature, you can have a wide view of the examination in progress on the computer display.

TECHNICAL DATA

Measurement system

Probe tones......226 Hz

678Hz. 800Hz. 1000Hz (Plus)

Compl. range..... 0.2 to 8.0 ml / 0.9 to 15.0 mmho

Pressure range... From -600 to +400 daPa

Man. pump contr. .. In tympanometry and reflex tests

Tympanometry

Type of test...... Automatic and manual tympanometry

Measures..... Admittance [Y]

Susceptance [B] (Plus)

Conductance [G] (Plus)

Press. change ... 15, 50, 100, 200, 300, 400, 600 daPa/sec, AUTO

Acoustic reflex

Stimulation....... Ipsi (I) and Contralateral (C)

Available tests... Autothreshold, Fixed intensity, Growing intensity

Manual test, Reflex decay, Reflex latency

Stimuli250 (contra), 500, 1k, 2k, 4k, 6k, 8k (contra) Hz
BBN, HPN, LPN

Maximum int. 110 dB HL (ipsi); 120 dB HL (contra)

Stim. duration....From 0.5 to 2.5 sec (selectable)

Reflex decay: 10 or 20 sec

Automatic tests...Quick A and B (seq. of tympan. and reflex)

ETF testIntact or perforated eardrums

Display type $\ldots\ldots$ Color graphical with touch screen

Display size / res.... 150 x 90 mm, 800 x 480 pixels

Printer.....Built-in thermal printer (optional)

PC interface.......USB (driverless)

Compatible soft...Inventis Daisy or Noah with dedicated module

Dimensions 32 x 32 x 15 cm – 12.6 x 12.6 x 5.9 inches (LxWxH)

Weight2.0 Kg / 4.4 lbs

Standards.....Tympan.: EN 60645-5 / ANSI S3.39, Type 1

Safety: EN 60601-1 EMC: EN 60601-1-2

Classification...... Class IIa (MDD 93/42)